New Installation for reducing the cost of water treatment

5way motorized control valve



Traditional installation:

There are 4set 2way control valve for one tank of general water filtering.



With 8pipes.







New installation:

Customers just need to purchase 1set 5way control valve for one tank, instead of 4set 2way control valve. It reduces the cost of design PLC and pipes material, also keep piping installation easily.



With 5 pipes.




Our new product 5 way control valve available for four function:

1. Filtering; 2. Backwashing; 3. Rinsing; 4. Sedimentation.

Application Industries:

Waste water treatment, fiber filter system (sand, tea, and wine...etc,) chemical treatment (iron, manganese, heavy metal removed...etc,) RO water treatment, soften water treatment, irrigation and drainage system, fish pool/swimming pool filtering system.









Diagram for 3" motorized control valve

Standard setting by our control box for three function:

1. Filtering; 2. Backwashing; 3. Rinsing.

Example for application



Application industries:

Waste water treatment, fiber filter system (sand, tea, and wine...etc), chemical treatment (iron, manganese, heavy metal removed...etc) RO water treatment, soften water treatment, irrigation and drainage system.



5way quarter turn motorized control valve

• Size:

1-1/2"~2" PT thread end;

• Available pressure: 10kgfcm2.

Material: VALVE – SS316 PTFE seat


Actuator housing-Nylon


• Voltage: AC220V single phase

- Standard function (control box):
 Filtering, Backwashing, Rinsing, Add salt,
 Sedimentation
- Patent:


NO.M530974 for PLC control box


NO.M489225 for packing ring on valve





NO.	Α	В	С	D	Е	Weight	ltem no.
SIZE					(Thread)	(Kg)	
1-1/2"	126.2	297	148	63	PT	9.86	UM-3-G3-AC220V-25W-5WAY-DN40
2"	181	320	169	74	PT	16.08	UM-3-G3-AC220V-25W-5WAY-DN50





5way quarter turn motorized control valve

• Size:

3"~4" JIS10K flange end;

• Available pressure: 10kgfcm2.

Material: VALVE – SS316 PTFE seat


Actuator housing-Nylon

• Voltage: AC220V single phase

- Standard function (control box):
 Filtering, Backwashing, Rinsing, Add salt,
 Sedimentation
- Patent:

NO.M530974 for PLC control box NO.M489225 for packing ring on valve





No.	Α	В	С	D	Е	Weight	Item no.
SIZE					(Flange)	(Kg)	
3"	371	558	308	145	JIS10K	60.15	UM-6-G3-AC220V-30W-5WAY-DN80
4"	490	673	348	152	JIS10K	102.50	UM-8-G3-AC220V-100W-5WAY-DN100

